

DECLARATION OF PERFORMANCE

No. 1/2023

1. Product-type:

Plywood for use as structural components in exterior conditions, technical class EN 636-3 S, from hard- and soft-wood, thickness from 9 mm to 35 mm

2. Identification of product:

Exterior plywood

3. Intended use or uses of the construction product:

Exterior plywood can be used in construction as structural components in exterior conditions

4. Name and address of the manufacturer:

SKLEJKA – EKO S.A.

str. Reymonta 35

63-400 Ostrów Wielkopolski

POLAND

5. Name and contact address of the authorized representative:

Not applicable

6. System of assessment and verification of constancy of performance of the construction product (AVCP):

System 2+

7. Notified Body's task(s), if applicable:

Material Testing Office of the country Brandenburg,

Department Wood and Wood-protection Eberswalde; Alfred – Möller – Strasse 1, 16225 Eberswalde

0763-CPR-6025

performed:

the initial inspection of the factory and of the factory production control and performs the continuous surveillance, assessment and approval of the factory production control

under system:

System 2+

and issued:

Certificate of Factory Production Control and Test report

8. Declared performance

Essential characteristics	Performance				Harmonized technical specification
Density	500 ÷ 750 kg/m ³				
Humidity	5 ÷ 12 %				
Bending strength along / across fibers	F 25/20 (38 / 30 N/mm ²)				
Modulus of elasticity along / across fibers	E 60/40 (5400 / 3600 N/mm ²)				
Compressive strenght	not tested				
Tensile strenght	not tested				
Release of formaldehyde	Class E1 ULEF				
Reaction to fire	PN-EN 13986+A1 tab. 8				
	D-s2,d0	without an air gap behind the wood-based panel	Density [kg/m ³]	Thickness [mm]	
			≥600	≥9	
			≥400	≥9 ≥12	
	D-s2,d2	with a closed or an open air gap not more than 22 mm behind the wood-based panel	≥600	≥9	
			≥400	≥9 ≥12	
	D-s2,d0 D-s2,d1 D-s2,d0	with a closed air gap behind the wood-based panel	≥600	≥15	
			≥400	≥15	
	D-s2,d0	with an open air gap behind the wood-based panel	≥400	≥18	
	E	any	≥400	≥3	
Water vapour permeability	Interpolated from EN 13986+A1 tab 9 for density 600 kg/m ³				
	μ wet cup	80	μ dry cup	210	

Airborne sound insulation	Calculated per EN13986+A1 section 5.10 using the formula (t = thickness in mm) $R=13 \times \lg (0,600 \times t)+14$	
Sound absorption coefficient	EN 13986+A1 tab. 10	
	250 – 500 Hz: 0,10	1000 – 2000 Hz: 0,30
Thermal conductivity	Interpolated from EN 13986+A1 tab 11 for density 600 kg/m ³ $\lambda=0,15 \text{ W}/(\text{m}\cdot\text{K})$	
Biological durability	Internal conditions, humid conditions (under shelter)	
Content of pentachlorophenol (PCP)	EN 13986+A1 section 5.18	< 5 ppm

9. The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 8.

This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4.

Signed for and on behalf of the manufacturer by:

TECHNOLOG
Nata
Natalia Weta

SKLEJKA-EKO S.A.
ul. Reymonta 35 (3a)
63-400 Ostrów Wlkp.
Regon 250005943
T. 022-330-391

.....
(name and function)

03.01.2023 **Ostrów Wielkopolski**

.....
(place and date of issue)

PREZES ZARZĄDU
DYREKTOR OPERACYJNY
Jacek Kaszyński

.....
(signature)